



THORNTON

Thornton
Eletrônica Ltda

NBC



Dimensões em mm

DESCRIÇÃO DE ENCOMENDA	MATERIAL	Ø D	Tol.	L	Tol.	PESO ~ g
NBC-1,63/5-TH50	TH50	1,63	± 0,05	5	± 0,20	0,048
NBC-1,65/5-TH50	TH50	1,65	± 0,05	5	± 0,20	0,049
NBC-1,7/8,4-IP6	IP6	1,70	- 0,20	8,4	- 0,30	0,075
NBC-1,7/8,4-TH50	TH50	1,70	- 0,20	8,4	- 0,30	0,075
NBC-1,78/8,4-TH50	TH50	1,78	- 0,20	8,4	- 0,30	0,075
NBC-3/10	IP12R	3	± 0,10	10	± 0,20	0,34
NBC-4,8/6,5-IP6	IP6	4,8	± 0,10	6,5	± 0,50	0,40
NBC-5/12-IP12R	IP12R	5	± 0,20	12	± 0,30	1,10
NBC-5/17-IP12R	IP12R	5	± 0,20	17	± 0,30	1,56
NBC-5/20-IP12R	IP12R	5	± 0,20	20	± 0,50	1,83
NBC-6/10-IP6	IP6	6	± 0,20	10	± 0,50	1,40
NBC-6/15-IP6	IP6	6	± 0,20	15	± 0,60	1,90
NBC-6/20-IP6	IP6	6	± 0,20	20	± 1,00	2,70
NBC-6/21-IP6	IP6	6	± 0,20	21	± 1,00	2,83
NBC-6/21-IP12R	IP12R	6	± 0,20	21	± 1,00	2,83
NBC-6/25-IP6	IP6	6	± 0,20	25	± 1,00	3,40
NBC-6/30-IP6	IP6	6	± 0,20	30	± 1,00	4,20
NBC-6/40-IP6	IP6	6	± 0,20	40	± 1,00	5,60
NBC-7,5/10-IP6	IP6	7,5	± 0,25	10	± 0,50	2,30
NBC-7,5/20-IP6	IP6	7,5	± 0,25	20	± 1,00	4,60
NBC-7,5/30-IP6	IP6	7,5	± 0,25	30	± 0,50	6,60
NBC-7,5/30-IP12R	IP12R	7,5	± 0,25	30	± 0,50	6,60
NBC-7,5/45-IP6	IP6	7,5	± 0,25	45	± 1,00	9,90
NBC-7,5/45-IP12R	IP12R	7,5	± 0,25	45	± 1,00	9,90
NBC-7,5/50-IP6	IP6	7,5	± 0,25	50	± 1,00	10,70
NBC-7,5/50-IP12R	IP12R	7,5	± 0,25	50	± 1,00	10,70
NBC-10/10-IP6	IP6	10	± 0,50	10	± 0,50	3,80
NBC-10/11-IP6	IP6	10	± 0,50	11	± 0,50	4,20
NBC-10/20-IP6	IP6	10	± 0,50	20	± 1,00	7,00
NBC-10/30-IP6	IP6	10	± 0,50	30	± 1,00	11,00
NBC-10/40-IP6	IP6	10	± 0,50	40	± 1,00	14,10
NBC-10/45-IP6	IP6	10	± 0,50	45	± 1,00	15,80
NBC-10/50-IP6	IP6	10	± 0,50	50	± 1,00	17,46
NBC-10/50-IP12R	IP12R	10	± 0,50	50	± 1,00	17,46
NBC-15/13,5-IP6	IP6	15	± 0,70	13,5	± 0,50	10,70
NBC-15/20-IP6	IP6	15	± 0,60	20	± 1,00	17,00
NBC-15/30-IP6	IP6	15	± 0,60	30	± 1,00	25,00
NBC-15/30-IP12R	IP12R	15	± 0,60	30	± 1,00	25,00
NBC-15/40-IP6	IP6	15	± 0,60	40	± 1,00	33,30
NBC-15/50-IP6	IP6	15	± 0,60	50	± 1,00	42,50